

PRODUCT SPECIFICATION

ITEM CODE: 3GB

3 TAP WATER DISPENSER

400GPD 5 stages under-sink RO system

- Feed water pressure: 0.1-0.35Mpa
- Operating pressure: 0.4-0.6Mpa
- Purified water flow rate: 1.05 L/min.
- Pure water against rejected water ratio: 1:1
- Rated voltage: 220V 50/60Hz
- Rated power consumption: 1800w
- Total water treatment capacity: 10000L
- Suitable feed water: residential tap water
- Suitable ambient temperature: 5 to 38 cent degree
- Suitable feed water TDS: 500ppm (maximum 2000ppm)



FILTERS:

- 1st Stage: 10" 5micron PP
- 2nd Stage: 10" Coconut Carbon Filter
- 3rd Stage: 10" Carbon Block Filter
- 4th Stage: 400G Dry Membrane
- 5th Stage: Post Carbon
- 6Gal Pressure Tank

Housing:

- Upper Cover: SS304, 1.0mm Thickness, Rim Folded Inside
- Outside Housing: SS201, 0.6mm Thickness
- Inner Tank: SS304, 1.2mm Thickness

PRODUCT SPECIFICATION

Cooling System:

- Type: Compressor cooling
- Control: Automatic temperature control
- Cold Tank: 10L, output capacity 30L/Hr at 6-8°C

Dimensions:

- Dimension: 1000 * 455 * 1180 mm
- Packing dimension: 1060 * 500 * 1200 mm

