


Cartridge Filters

Spun Polypropylene Sediment Filter Cartridges

Pure Aqua's spun polypropylene sediment filters are constructed of multi-layers for superior depth filtration. The graded density construction captures particles throughout the entire cross section of the cartridge and reduces surface binding. The cartridges combine quality and cost effectiveness to provide excellent filtration value. Available in a variety of micron ratings and sizes. Pure Aqua's spun polypropylene sediment filters meet NSF standards.





Applications

- Reverse osmosis pre-filtration
- Food & beverage industry
- Potable water
- Electronics
- Residential
- Fine chemicals
- Plating
- Metal finishing
- Car wash



2.5" Diameter

Part Number	Micron	Length
PPS10	1	10"
PP10	5	10"
PPS20	1	20"
PP20	5	20"
PP20-50	50	20"
PPS30	1	30"
PP30	5	30"
PPS40	1	40"
PP40	5	40"

Features & Benefits

- Multi-layers graded density
- Excellent chemical resistance
- Low cost
- High dirt holding capacity
- Wide range of micron ratings
- Wide range of sizes

Specifications

Material	Polypropylene		
Length	9-7/8" - 40"		
Maximum temperature	60°C / 140°F		
Micron rating (nominal)	1 - 50		
Maximum flow rate	2 - 28 gpm (2.5" diameter)	10 - 30 gpm (4.5" diameter)	
Cartridge packaging	Shrink wrapped		

4.5" Diameter

Part Number	Micron	Length
PP10BB	5	10"
PP20BB	5	20"
PP20BB-1	1	20"